Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

(Currently Amended) A method of coating a medical implant comprising:
 placing a <u>reconfigurable</u> medical implant into a rotatable drum <u>having a plurality of</u>
 orifices in a wall;

tumbling the medical implant by rotating the drum about a longitudinal axis of the drum;

placing therapeutic into the drum by moving the therapeutic through a channel positioned in the drum, the channel containing a plurality of orifices; and interfacing the therapeutic with the tumbling medical implant.

- 2. (Original) The method of claim 1, further comprising: drying the therapeutic on the medical implant.
- 3. (Original) The method of claim 2, wherein drying the therapeutic on the medical implant includes spraying an inert gas into the drum.
- 4. (Original) The method of claim 1, further comprising: suspending the medical implants above an internal surface of the drum.
- 5. (Previously Presented) A method for applying a coating to a medical implant comprising:

providing a pan coater, the pan coater including a drum having a bottom and a wall; placing a reconfigurable medical implant in the drum of the pan coater, the medical implant having a masking material on at least one of its surfaces, the medical implant free to strike at least the bottom or wall of the drum;

rotating the drum about an axis to tumble the medical implant, the drum containing a plurality of orifices in the wall;

spraying a therapeutic into the drum to coat the medical implant; and removing the medical implant from the drum.

6. (Previously Presented) The method of claim 5, further comprising: collecting therapeutic in a therapeutic recovery reservoir fluidly attached to the drum.

7. (Currently Amended) A method for applying a coating to a medical implant comprising:

providing a pan coater, the pan coater including a drum having a bottom and a wall; placing a <u>reconfigurable</u> medical implant in the drum of the pan coater;

rotating the drum about an axis, to tumble the medical implant, the drum containing a plurality of orifices in the wall;

spraying a therapeutic into the drum to coat the medical implant;

forcing a compressible fluid from a compressible fluid source into the drum to dry the therapeutic;

re-circulating the compressible fluid in the drum; and

waiting until the therapeutic on the medical implant is dry before removing the medical implant from the drum.

- 8. (Previously Presented) The method of claim 5, wherein spraying the therapeutic into the drum is repeated at least once.
- 9. (Currently Amended) A method for applying a coating to a medical implant comprising:

providing a pan coater, the pan coater including a drum having a bottom and a wall; placing a reconfigurable medical implant in the drum of the pan coater;

rotating the drum about an axis, to tumble the medical implant, the drum containing a plurality of orifices in the wall;

spraying a therapeutic into the drum to coat the medical implant;

forcing a compressible fluid from a compressible fluid source into the drum;

re-circulating the compressible fluid in the drum;

waiting until the therapeutic on the medical implant is dry before removing the medical implant from the drum; and

heating the compressible fluid in the compressible fluid source prior to forcing the compressible fluid into the drum.

Appln. No. 10/087,014 Amendment filed with RCE

- 10. (Original) The method of claim 9, wherein the compressible fluid in the compressible fluid source is heated to a temperature in the range of 20 to 70 degrees centigrade.
- 11. (Original) The method of claim 9, wherein the compressible fluid in the compressible fluid source is heated to a temperature associated with a working temperature of the therapeutic.
- 12. (Currently Amended) A method for applying a coating to a medical implant comprising:

providing a pan coater, the pan coater including a drum having a bottom and a wall;

placing a reconfigurable medical implant in the drum of the pan coater;

rotating the drum about an axis to tumble the medical implant, the drum containing a

plurality of orifices in the wall;

spraying a therapeutic into the drum to coat the medical implant; drawing a compressible fluid into the drum; and removing the medical implant from the drum.

13. (Currently Amended) A method for applying a coating to a medical implant comprising:

providing a pan coater, the pan coater including a drum having a bottom and a wall;

placing a reconfigurable medical implant in the drum of the pan coater;

rotating the drum about an axis to tumble the medical implant, the drum containing a plurality of orifices in the wall;

spraying a therapeutic into the drum to coat the medical implant; heating the rotatable drum after spraying the therapeutic into the drum; and removing the medical implant from the drum.

14. (Original) The method of claim 5, wherein the pan coater is provided with a compressible fluid suspension system that forces a compressible fluid into the drum with a force sufficient to maintain the medical implant aloft in the drum.

- 15. (Original) The method of claim 14, wherein the compressible fluid suspension system uses an inert gas to maintain the medical implants aloft.
- 16. (Original) The method of claim 14, further comprising: periodically activating the compressible fluid suspension system.
- 17. (Canceled)
- 18. (Previously Presented) The method of claim 5, further comprising: passing therapeutic through the orifices; and passing compressible fluid through the orifices.
- 19. (Currently Amended) A method for applying a coating to a medical implant comprising:

providing a pan coater, the pan coater including a drum having a bottom and a wall; placing a <u>reconfigurable</u> medical implant in the drum of the pan coater;

rotating the drum about an axis, to tumble the medical implant, the drum containing a plurality of orifices in the wall;

spraying a first therapeutic into the drum to coat the medical implant; spraying a second therapeutic into the drum after spraying the first therapeutic into the drum, the second therapeutic different from the first therapeutic;

recycling therapeutic that did not adhere to the implant during spraying.

20-24. (Canceled)

25. (Previously Presented) A method for applying a coating to a medical implant comprising:

providing a pan coater, the pan coater including a drum rotatable about a longitudinal axis having a wall and a bottom, the wall having a plurality of orifices;

placing a reconfigurable medical implant in the drum of the pan coater;

injecting a compressible fluid into the drum with a force sufficient to maintain the medical implant aloft in the drum to tumble the medical implant, the medical implant being free to strike at least the bottom or wall of the drum;

spraying a therapeutic into the drum to coat the medical implant; and removing the medical implant from the drum.

- 26. (Original) The method of claim 25, wherein the compressible fluid is an inert gas.
- 27. (Original) The method of claim 25, wherein the compressible fluid is also for drying the therapeutic on the medical implant.
- 28. (Previously Presented) The method of claim 25 wherein the compressible fluid is periodically injected into the drum.
- 29. (Currently Amended) A method of coating a medical implant comprising:

 placing a reconfigurable medical implant into a rotatable drum;

 tumbling the medical implant by rotating the drum about a longitudinal axis of the drum;

placing therapeutic into the drum by moving the therapeutic through a <u>plurality of</u> orifices <u>channel</u> positioned [[in]] on the drum; and

interfacing the therapeutic with the tumbling medical implant wherein interfacing the therapeutic with the tumbling implant includes tumbling the implant into a vat of therapeutic.

- 30. (Canceled)
- 31. (Currently Amended) The method of claim 30-1 wherein the reconfigurable medical implant is a stent.
- 32. (Canceled)

- 33. (Currently Amended) The method of claim 3212 wherein the reconfigurable medical implant is a stent.
- 34. (Canceled)
- 35. (Currently Amended) The method of claim 3413 wherein the reconfigurable medical implant is a stent.
- 36. (Canceled)
- 37. (Currently Amended) The method of claim 367 wherein the reconfigurable medical implant is a stent.
- 38. (Canceled)
- 39. (Currently Amended) The method of claim 38-9 wherein the reconfigurable medical implant is a stent.
- 40. (New) The method of claim 5 wherein the therapeutic is sprayed into the drum through at least one nozzle positioned on the wall of the drum.
- 41. (New) The method of claim 40 wherein the nozzle is controlled by a processor having storage media.
- 42. (New) The method of claim 5 wherein the therapeutic is sprayed into the drum through at least one nozzle positioned on the bottom of the drum.
- 43. (New) The method of claim 42 wherein the nozzle is controlled by a processor having storage media.

- 44. (New) The method of claim 6 wherein the therapeutic recovery reservoir is connected to the drum via a dual use channel and the dual use channel is also connected to a compressible fluid source.
- 45. (New) The method of claim 5 wherein the drum has a removable lid.